

PGM BaseFunction Base

QPGM Search

System ID & Numbering Plans

Station Data

Board Based Data

H.323 VoIP Attributes(130)

T1/E1/PRI Attributes(131)

Board Base Attributes(132)

CO Line Data

System Data

Station Group Data

ISDN Line Data

SIP Data

Tables Data

Favorite PGMH.323 VoIP Attributes(130)Board Base Attributes(132)

Enter Device/GW Slot Sequence Range (1 - 2890) :

?

Load

Device/Gateway Sequence(Slot) Range 1

Order	Uncheck All	Attribute	Value	Range
1	<input checked="" type="checkbox"/>	Router IP Address		IP Address
2	<input checked="" type="checkbox"/>	Device Codec Type	System Codec	
3	<input checked="" type="checkbox"/>	Firewall IP Address		IP Address
4	<input checked="" type="checkbox"/>	RTP Packet Relay Firewall IP Address		IP Address
5	<input checked="" type="checkbox"/>	RTP Security	ON	
6	<input checked="" type="checkbox"/>	T-NET Enable	OFF	
7	<input checked="" type="checkbox"/>	T38 Enable	OFF	
8	<input checked="" type="checkbox"/>	USE Board IP for SIP	OFF	
9	<input checked="" type="checkbox"/>	T38 Port Usage	DIFF WITH VOICE	
10	<input checked="" type="checkbox"/>	RFC2833 Payload	101	0-127
11	<input checked="" type="checkbox"/>	RFC2833 Volume	10	0-36(-dB)
12	<input checked="" type="checkbox"/>	RFC2833 Redundancy	4	1-8